hp LaserJet 4345mfp series

configuration page 1

Device Information

Product Name: hp LaserJet 4345 mfp
Device Name: hp LaserJet 4345 mfp
Model Number: Q3943A
DC Controller: 17
Device Serial Number: CNHYF00713
Formatter Number: D810XSE
CPB: 0.209 (2.0)
SCB: CMNPSL 28
Firmware Datecode: 20090605 09.141.4
Service ID: 15255
PS Wait Time-out: 300 seconds
Page Count: 114191
Maintenance Kit Interval: 225000
Pages Since Last Maintenance: 114069
Document Feeder Kit Interval: 90000
Pages Since Last Doc Feeder Maintenance: 1279

Installed Personalities and Options

PCLXL (20010402)
PCL (20010402)
PDF (20021216)
XHTML (700)
MIME (700)
PS (20010402)
IOF 1(-): ThinPrint(active) (20050315) 005
DIMM Slot 1: Empty
DIMM Slot 2: 256 MB DDR
Card Slot 1: 32 MB F/W FLASH: 1 MB
Card Slot 2: EuroForm ThinPrint: 31 MB
Card Slot 3: Empty
EIO 1: Empty
EIO 2: HP Scanner Processor Card
Internal Disk: HP J7948A: 18 GB
Internal Fax
Embedded HP JetDirect J7949E
LDAP Gateway: 0.0.0.0
SMTP Gateway: 0.0.0.0
hp MFP Digital Sending Server: 0.0.0.0

Memory

Total RAM: 256 MB
DWS: 6.00
Automatic Resource Saving Enabled

Event Log

Number of Entries in Use: 50
Maximum Number of Entries: 50
Three Most Recent Entries:

Number	Page Count	Entry
50	114190	10.10.00
49	114088	49 4C45
48	113728	49 4C45

Security

Control Panel Lock: NONE
Control Panel Password: DISABLED
Write Protect: DISABLED
File System Access:
PJL: ENABLED
PML: ENABLED
NFS: ENABLED
PostScript: ENABLED
Secure Disk Erase Mode: NON-SECURE FAST ERASE
Direct Connect Ports (USB/IEEE 1284): ENABLED

Paper Trays and Options

Default Paper Size: A4
Tray 1 Size: ANY SIZE
Tray 2 Size: A4
Tray 3 Size: A4
Duplex Unit

hp LaserJet 4345mfp series

Fax Accessory Page 1

HARDWARE INFORMATION

PRODUCT: LT V.92 1.0 MT5634SMI-V92 Data/Fax Modem
MODEM FIRMWARE VERSION: 2.37m
MODEM STATUS: OPERATIONAL / ENABLED

FAX INFORMATION

FAX JOB COUNT: 729

FAX SETUP SETTINGS

LOCATION: RUSSIA
DATE FORMAT: DD/MMM/YYYY
CURRENT DATE: 22-Feb-2014
TIME FORMAT: 12-HR (AM/PM)
CURRENT TIME: 01:47 PM
PHONE NUMBER: None
COMPANY NAME: None
MODEM VOLUME: MEDIUM
RINGER VOLUME: MEDIUM
ERROR CORRECTION: ON
JBIG COMPRESSION: ON
RING BURST OFF TIME: DEFAULT
RING FREQUENCY: DEFAULT
TCF T.30 DELAY: DEFAULT
TCF EXTEND: DEFAULT

FAX SEND SETTINGS

DEFAULT RESOLUTION: STANDARD
OVERLAY HEADER: NO
DIALING MODE: TONE
REDIAL ON BUSY: 3
REDIAL ON NO ANSWER: 0
REDIAL INTERVAL: 5
DETECT DIAL TONE: OFF
DIAL PREFIX: OFF
PREFIX:
PC FAX SEND: ENABLED
BILLING CODE: OFF
BILLING CODE DIGITS: 1

FAX RECEIVE SETTINGS

RINGS TO ANSWER: 2
STAMP RECEIVED FAXES: NO
FIT TO PAGE: YES
FAX PAPER TRAY: 0
FAX DESTINATION BIN: 0
FORWARD FAX NUMBER:
FAX PRINTING: ON

FAX REPORT SETTING

FAX CALL REPORT: NEVER
THUMBNAIL ON CALL REPORT: NO
FAX T.30 TRACER REPORT: NEVER

hp LaserJet 4345mfp series

Embedded Jetdirect Page 1

--------- General Information ----------

Status:	I/O Card Not Ready
LAN ERROR - LOSS OF CARRIER	
Model Number:	J7949E
Hardware Address:	001279DE7D1C
Firmware Version:	V.33.19.FF
LAA:	001279DE7D1C
Port Config:	Disconnected
Auto Negotiation:	On
Manufacturing ID:	4508450800****
Date Manufactured:	02/2005

---------- Security Settings ----------

802.1X:	Not Specified
Admin Password:	Not Specified
Secure Web:	HTTPS Optional
Cert Expires:	2010-02-01 00:00 UTC
SNMP Versions:	1;2
SNMP Set Cmty Name:	Not Specified
Access List:	Not Specified

---------- Network Statistics ----------

Total Packets Received:	0
Unicast Packets Received:	0
Bad Packets Received:	0
Framing Errors Received:	0
Total Packets Transmitted:	0
Unsendable Packets:	0
Transmit Collisions:	0
Transmit Late Collisions:	0

---------- TCP/IP ----------

Status:	Initializing
Host Name:	Not Specified
IPv4 Domain Name:	Not Specified
Primary DNS Server:	Not Specified
Secondary DNS Server:	Not Specified
WINS Server:	Not Specified
Idle Timeout:	90 sec

---------- IPv4 ----------

IP Address:	0.0.0.0
Subnet Mask:	0.0.0.0
Default Gateway:	0.0.0.0
Config By:	Not Configured
BOOTP/DHCP Server:	0.0.0.0
TFTP Server:	0.0.0.0
Web Jetadmin URL:	Not Specified
mDNS Service Name:	Not Specified

hp LaserJet 4345mfp series

Embedded Protocol Page 1

---------- IPX/SPX ----------
Status: Initializing

Primary Frame Type: Auto Select

Network Frame Type Rcvd

---------- Novell/NetWare ----------
Status: 16
NOT CONFIGURED
Node Name: NPIDE7D1C

NetWare Mode: Queue Server
NDS Tree Name:

NDS Context:

SAP Interval: 60 sec
Attached Server:

---------- AppleTalk ----------
Status: Initializing

Name:
Zone: *
Type 1: HP LaserJet
Type 2: LaserWriter
Network Number: 0
Node Number: 0

---------- DLC/LLC ----------
Status: Initializing

hp LaserJet 4345mfp series

supplies status page 1

Non-HP Black Cartridge*
Order HP Part: Q5945A

ATTENTION: A non Hewlett-Packard supply has been installed. To ensure full availability of printing features (such as remaining supply status), use genuine HP supplies.

*(See Warranty Note)

Maintenance Kit 50%
Order HP Part: 110V-Q5998A, 220V-Q5999A



Document Feeder Kit 99%
Order HP Part: Q5997A



***Warranty Note**

ATTENTION: A non Hewlett-Packard supply has been detected. Service or repairs required as a result of using a non Hewlett-Packard supply will NOT be covered under device warranty.

Using genuine HP supplies ensures full availability of printing features.

If this cartridge was sold to you as a genuine HP product, then please call our fraud hot-line. (Refer to your device User Guide for the telephone number).

Ordering Information

Hewlett-Packard supplies can be ordered on the Internet, on-line through your device software, or by calling an authorized reseller. Refer to your User Guide for instructions.

Return & Recycling

Please return your genuine HP supplies for recycling to Hewlett-Packard. For more information, please visit us at http://www.hp.com/go/recycle